


Fachlast / Feldlast










B = 1825 mm (RTP-080)




	2 x		3 x		4 x		5 x		6 x	
Fachhöhe	Fachlast	Feldlast	Fachlast	Feldlast	Fachlast	Feldlast	Fachlast	Feldlast	Fachlast	Feldlast
T = 1100 mm (H20)										
770 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2700 kg	13500 kg	2200 kg	13200 kg
910 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2700 kg	13500 kg	2200 kg	13200 kg
1120 mm	3000 kg	6000 kg	3000 kg	9000 kg	2900 kg	11600 kg	2500 kg	12500 kg	-	-
1330 mm	3000 kg	6000 kg	3000 kg	9000 kg	2700 kg	10800 kg	2300 kg	11500 kg	-	-
1540 mm	3000 kg	6000 kg	2900 kg	8700 kg	2500 kg	10000 kg	-	-	-	-
1890 mm	3000 kg	6000 kg	2700 kg	8100 kg	-	-	-	-	-	-
2310 mm	2900 kg	5800 kg	-	-	-	-	-	-	-	-
T = 900 mm (H20)										
770 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2700 kg	13500 kg	2200 kg	13200 kg
910 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2700 kg	13500 kg	2200 kg	13200 kg
1120 mm	3000 kg	6000 kg	3000 kg	9000 kg	2900 kg	11600 kg	2500 kg	12500 kg	-	-
1330 mm	3000 kg	6000 kg	3000 kg	9000 kg	2700 kg	10800 kg	2300 kg	11500 kg	-	-
1540 mm	3000 kg	6000 kg	2900 kg	8700 kg	2500 kg	10000 kg	-	-	-	-
1890 mm	3000 kg	6000 kg	2700 kg	8100 kg	-	-	-	-	-	-
2310 mm	2900 kg	5800 kg	-	-	-	-	-	-	-	-
T = 750 mm (H20)										
770 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2700 kg	13500 kg	2200 kg	13200 kg
910 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2700 kg	13500 kg	2200 kg	13200 kg
1120 mm	3000 kg	6000 kg	3000 kg	9000 kg	2900 kg	11600 kg	2500 kg	12500 kg	-	-
1330 mm	3000 kg	6000 kg	3000 kg	9000 kg	2700 kg	10800 kg	2300 kg	11500 kg	-	-
1540 mm	3000 kg	6000 kg	2900 kg	8700 kg	2500 kg	10000 kg	-	-	-	-
1890 mm	3000 kg	6000 kg	2700 kg	8100 kg	-	-	-	-	-	-
2310 mm	2900 kg	5800 kg	-	-	-	-	-	-	-	-



Fachlast / Feldlast



 B = 2700 mm (RTP-110)   $\geq 4 \times B$										
	 2 x		 3 x		 4 x		 5 x		 6 x	
Fachhöhe	Fachlast	Feldlast	Fachlast	Feldlast	Fachlast	Feldlast	Fachlast	Feldlast	Fachlast	Feldlast
T = 1100 mm (H20)										
770 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2700 kg	13500 kg	2200 kg	13200 kg
910 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2700 kg	13500 kg	2200 kg	13200 kg
1120 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2600 kg	13000 kg	-	-
1330 mm	3000 kg	6000 kg	3000 kg	9000 kg	2900 kg	11600 kg	2400 kg	12000 kg	-	-
1540 mm	3000 kg	6000 kg	3000 kg	9000 kg	2700 kg	10800 kg	-	-	-	-
1890 mm	3000 kg	6000 kg	3000 kg	9000 kg	-	-	-	-	-	-
2310 mm	3000 kg	6000 kg	-	-	-	-	-	-	-	-
T = 900 mm (H20)										
770 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2700 kg	13500 kg	2200 kg	13200 kg
910 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2700 kg	13500 kg	2200 kg	13200 kg
1120 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2600 kg	13000 kg	-	-
1330 mm	3000 kg	6000 kg	3000 kg	9000 kg	2900 kg	11600 kg	2400 kg	12000 kg	-	-
1540 mm	3000 kg	6000 kg	3000 kg	9000 kg	2700 kg	10800 kg	-	-	-	-
1890 mm	3000 kg	6000 kg	3000 kg	9000 kg	-	-	-	-	-	-
2310 mm	3000 kg	6000 kg	-	-	-	-	-	-	-	-
T = 750 mm (H20)										
770 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2700 kg	13500 kg	2200 kg	13200 kg
910 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2700 kg	13500 kg	2200 kg	13200 kg
1120 mm	3000 kg	6000 kg	3000 kg	9000 kg	3000 kg	12000 kg	2600 kg	13000 kg	-	-
1330 mm	3000 kg	6000 kg	3000 kg	9000 kg	2900 kg	11600 kg	2400 kg	12000 kg	-	-
1540 mm	3000 kg	6000 kg	3000 kg	9000 kg	2700 kg	10800 kg	-	-	-	-
1890 mm	3000 kg	6000 kg	3000 kg	9000 kg	-	-	-	-	-	-
2310 mm	3000 kg	6000 kg	-	-	-	-	-	-	-	-

Fachlast / Feldlast



 B = 3600 mm (RTP-160)  										
										
Fachhöhe	Fachlast	Feldlast	Fachlast	Feldlast	Fachlast	Feldlast	Fachlast	Feldlast	Fachlast	Feldlast
T = 1100 mm (H20)										
770 mm	3400 kg	6800 kg	3400 kg	10200 kg	3200 kg	12800 kg	2700 kg	13500 kg	2300 kg	13800 kg
910 mm	3400 kg	6800 kg	3400 kg	10200 kg	3200 kg	12800 kg	2700 kg	13500 kg	2300 kg	13800 kg
1120 mm	3400 kg	6800 kg	3300 kg	9900 kg	3200 kg	12800 kg	2600 kg	13000 kg	-	-
1330 mm	3400 kg	6800 kg	3300 kg	9900 kg	3000 kg	12000 kg	2500 kg	12500 kg	-	-
1540 mm	3400 kg	6800 kg	3200 kg	9600 kg	2900 kg	11600 kg	-	-	-	-
1890 mm	3300 kg	6600 kg	3000 kg	9000 kg	-	-	-	-	-	-
2310 mm	3200 kg	6400 kg	-	-	-	-	-	-	-	-
T = 900 mm (H20)										
770 mm	3400 kg	6800 kg	3400 kg	10200 kg	3200 kg	12800 kg	2700 kg	13500 kg	2200 kg	13200 kg
910 mm	3400 kg	6800 kg	3400 kg	10200 kg	3200 kg	12800 kg	2700 kg	13500 kg	2200 kg	13200 kg
1120 mm	3400 kg	6800 kg	3300 kg	9900 kg	3200 kg	12800 kg	2600 kg	13000 kg	-	-
1330 mm	3400 kg	6800 kg	3300 kg	9900 kg	3000 kg	12000 kg	2500 kg	12500 kg	-	-
1540 mm	3400 kg	6800 kg	3200 kg	9600 kg	2900 kg	11600 kg	-	-	-	-
1890 mm	3300 kg	6600 kg	3000 kg	9000 kg	-	-	-	-	-	-
2310 mm	3200 kg	6400 kg	-	-	-	-	-	-	-	-
T = 750 mm (H20)										
770 mm	3400 kg	6800 kg	3400 kg	10200 kg	3200 kg	12800 kg	2700 kg	13500 kg	2200 kg	13200 kg
910 mm	3400 kg	6800 kg	3400 kg	10200 kg	3200 kg	12800 kg	2700 kg	13500 kg	2200 kg	13200 kg
1120 mm	3400 kg	6800 kg	3300 kg	9900 kg	3200 kg	12800 kg	2600 kg	13000 kg	-	-
1330 mm	3400 kg	6800 kg	3300 kg	9900 kg	3000 kg	12000 kg	2500 kg	12500 kg	-	-
1540 mm	3400 kg	6800 kg	3200 kg	9600 kg	2900 kg	11600 kg	-	-	-	-
1890 mm	3300 kg	6600 kg	3000 kg	9000 kg	-	-	-	-	-	-
2310 mm	3200 kg	6400 kg	-	-	-	-	-	-	-	-

Rahmenlast

Reduktionsfaktoren für Anzahl an Regalfeldern <4

- 1 Feld: Reduktionsfaktor = 80 %
- 2 Felder: Reduktionsfaktor = 85 %
- 3 Felder: Reduktionsfaktor = 90 %

Beispiel:



T = 1100 mm
A = 1540 mm
B = 1825 mm
2 x B

Max Σ kg = 8800 kg x 85 %
= 7480 kg



! B = 1825 mm (RTP-080)  ≥ 4 x B					
	2 x 	3 x 	4 x 	5 x 	6 x 
Fachhöhe	Rahmenlast				
T = 1100 mm (H20)					
770 mm	6700 kg	9900 kg	13100 kg	14400 kg	14700 kg
910 mm	6600 kg	9800 kg	12600 kg	13700 kg	13900 kg
1120 mm	6600 kg	9500 kg	11800 kg	12700 kg	-
1330 mm	6500 kg	9200 kg	11100 kg	11800 kg	-
1540 mm	6400 kg	8800 kg	10300 kg	-	-
1890 mm	6100 kg	8100 kg	-	-	-
2310 mm	5800 kg	-	-	-	-
T = 900 mm (H20)					
770 mm	6700 kg	9900 kg	13100 kg	14400 kg	14700 kg
910 mm	6700 kg	9800 kg	12600 kg	13700 kg	13900 kg
1120 mm	6600 kg	9500 kg	11800 kg	12700 kg	-
1330 mm	6500 kg	9200 kg	11100 kg	11800 kg	-
1540 mm	6400 kg	8800 kg	10300 kg	-	-
1890 mm	6100 kg	8100 kg	-	-	-
2310 mm	5800 kg	-	-	-	-
T = 750 mm (H20)					
770 mm	6700 kg	9900 kg	13100 kg	14400 kg	14700 kg
910 mm	6700 kg	9800 kg	12600 kg	13700 kg	13900 kg
1120 mm	6600 kg	9500 kg	11800 kg	12700 kg	-
1330 mm	6500 kg	9200 kg	11100 kg	11800 kg	-
1540 mm	6400 kg	8800 kg	10300 kg	-	-
1890 mm	6100 kg	8100 kg	-	-	-
2310 mm	5800 kg	-	-	-	-

Rahmenlast

Reduktionsfaktoren für Anzahl an Regalfeldern <4

- 1 Feld: Reduktionsfaktor = 80 %
- 2 Felder: Reduktionsfaktor = 85 %
- 3 Felder: Reduktionsfaktor = 90 %


Beispiel:



T = 1100 mm
A = 1540 mm
B = 2700 mm
2 x B

Max Σ kg = 9600 kg x 85 %
= 8160 kg



! B = 2700 mm (RTP-110)  ≥ 4 x B					
	2 x 	3 x 	4 x 	5 x 	6 x 
Fachhöhe	Rahmenlast				
T = 1100 mm (H20)					
770 mm	6600 kg	9900 kg	14100 kg	14400 kg	14300 kg
910 mm	6600 kg	9900 kg	13500 kg	13900 kg	13700 kg
1120 mm	6600 kg	9900 kg	12600 kg	13000 kg	-
1330 mm	6600 kg	9800 kg	11800 kg	12200 kg	-
1540 mm	6600 kg	9600 kg	11000 kg	-	-
1890 mm	6500 kg	9000 kg	-	-	-
2310 mm	6300 kg	-	-	-	-
T = 900 mm (H20)					
770 mm	6600 kg	9900 kg	14100 kg	14400 kg	14300 kg
910 mm	6600 kg	9900 kg	13500 kg	13800 kg	13800 kg
1120 mm	6600 kg	9900 kg	12600 kg	13000 kg	-
1330 mm	6600 kg	9800 kg	11800 kg	12200 kg	-
1540 mm	6600 kg	9600 kg	11000 kg	-	-
1890 mm	6500 kg	9000 kg	-	-	-
2310 mm	6300 kg	-	-	-	-
T = 750 mm (H20)					
770 mm	6600 kg	9900 kg	14100 kg	14400 kg	14300 kg
910 mm	6600 kg	9900 kg	13500 kg	13800 kg	13800 kg
1120 mm	6600 kg	9900 kg	12600 kg	13000 kg	-
1330 mm	6600 kg	9800 kg	11800 kg	12200 kg	-
1540 mm	6600 kg	9600 kg	11000 kg	-	-
1890 mm	6500 kg	9000 kg	-	-	-
2310 mm	6300 kg	-	-	-	-

Rahmenlast

Reduktionsfaktoren für Anzahl an Regalfeldern <4

- 1 Feld: Reduktionsfaktor = 80 %
- 2 Felder: Reduktionsfaktor = 85 %
- 3 Felder: Reduktionsfaktor = 90 %

Beispiel:



T = 1100 mm
A = 1540 mm
B = 3600 mm
2 x B

Max Σ kg = 9600 kg x 85 %
= 8160 kg



! B = 3600 mm (RTP-160) ≥ 4 x B					
	2 x	3 x	4 x	5 x	6 x
Fachhöhe	Rahmenlast				
T = 1100 mm (H20)					
770 mm	6900 kg	10400 kg	13600 kg	14100 kg	14500 kg
910 mm	6900 kg	10300 kg	13200 kg	13700 kg	14000 kg
1120 mm	6900 kg	10100 kg	12700 kg	13100 kg	-
1330 mm	6800 kg	9800 kg	12200 kg	12500 kg	-
1540 mm	6700 kg	9600 kg	11600 kg	-	-
1890 mm	6600 kg	9100 kg	-	-	-
2310 mm	6300 kg	-	-	-	-
T = 900 mm (H20)					
770 mm	6900 kg	10400 kg	13600 kg	14100 kg	14400 kg
910 mm	6900 kg	10300 kg	13200 kg	13700 kg	13900 kg
1120 mm	6900 kg	10100 kg	12700 kg	13100 kg	-
1330 mm	6800 kg	9800 kg	12200 kg	12400 kg	-
1540 mm	6700 kg	9600 kg	11600 kg	-	-
1890 mm	6600 kg	9100 kg	-	-	-
2310 mm	6300 kg	-	-	-	-
T = 750 mm (H20)					
770 mm	6900 kg	10400 kg	13600 kg	14100 kg	14300 kg
910 mm	6900 kg	10300 kg	13200 kg	13700 kg	13800 kg
1120 mm	6900 kg	10100 kg	12700 kg	13000 kg	-
1330 mm	6800 kg	9800 kg	12200 kg	12400 kg	-
1540 mm	6700 kg	9600 kg	11600 kg	-	-
1890 mm	6600 kg	9100 kg	-	-	-
2310 mm	6300 kg	-	-	-	-

Sie haben Fragen? Rufen Sie uns an unter: **02351 / 98 80-88**